

OpenSynergy provides a next-generation hypervisor, enabling the secure convergence of software functions with very different safety and security requirements. The new hypervisor achieves this by generating virtual machines (VMs) where multi-purpose operating systems such as Linux or Android can coexist and interact with real-time operating systems (RTOS). It boasts a minimalistic design for high efficiency and flexibility. These benefits stem in large part from a lean kernel and support for hardware virtualization.

Benefits

- Trusted code base with small footprint
- Designed and optimized for next-generation processor architectures
- Minimal performance overhead
- Developed for ASIL-B compliance underpinned by Automotive Spice Level 3
- Tailored to the needs of automotive use cases
- Based on OpenSynergy's long-term experience in hypervisor technology in the automotive domain.
- Supports flexible hardware resource management

Features

- Designed for mixed criticality systems
- Supports multicore guest VM's
- Enables integration of arbitrary guest operating systems
- Innovative scheduler provides both realtime and fair share simultaneously
- Highly efficient, low overhead inter-VM communication

Supported Hardware

Architecture


- ARMv7VE-A
- ARMv8-A

Reference SoC

- Qualcomm® Snapdragon™ SA 8155P and early available SA 8295

Supported SoCs with essential features

- NXP® i.MX 8
- NXP® S32G
- Renesas R-Car H3/M3
- Samsung Exynos V910
- TI Jacinto™ 7
- Any other ARMv8-A SoC can be supported on customer request



Core Parts

Full OS Flexibility

- Unmodified core system
- No need of paravirtualization of guest OS

Hypervisor Configuration and Platform Integration

- Static configuration
- Model based configuration
 - Configuration of hypervisor binary
 - Runtime configuration for hypervisor and guests
- Human understandable model
- Tools guarantee consistent configuration data
- Configuration tools easily integrate to customer build environment

Strong Separation

- Memory protection
- Scheduling
- Device access

Scheduling

- Highly predictable scheduling for real-time OS (e.g. AUTOSAR or other RTOS's)
- High performance for non-real-time OS (e.g. Linux, Android)

System Startup

Early functions first (fast-boot) to satisfy boot time requirements:

- Controlled boot order: Early functions start rapidly (e.g. RVC, CAN)
- Modular boot: Orchestration of boot regime

Security

- Secure boot
- Inter-VM communication configuration cannot be bypassed
- Integration of platform security (secure boot, encrypted storage, TrustZone)

Safety and Reliability

- Design guided by safety requirements
- Small code size, below 10k SLOC due to low complexity kernel architecture

ISO 26262

TÜV-Süd has confirmed that the COQOS Hypervisor meets the requirements of ISO 26262 up to ASIL-B and has issued an associated Technical Report.

Kernel Architecture

- Multi-kernel architecture supports multicore SoCs efficiently
- Supports SMP guest OS
- Low complexity allows for affordable certification

Power Management

- Complexity awareness
- Provides passive power management functions

Optional Parts

System Supervisor

A configurable watchdog (contained in a separate partition) can observe the behavior of specific applications, and take action when the system does not behave correctly.

CAN Gateway

The CAN Gateway is a minimalistic AUTOSAR stack, that contains:

- a full AUTOSAR OS implementation
- a full CAN Driver
- partial AUTOSAR CAN stack (Com, PduR, Canif)
- minimalistic RTE implementation
- OpenSynergy's AUTOSAR Configurator automatically configure the CAN Gateway stack based on a CAN-CFG file (DSL describing the CAN DB)
- ACF "Automotive Communication Framework" which is a CDD responsible on communication between AUTOSAR and non-AUTOSAR partitions.

Linux and Android Support

The hypervisor supports the latest linux versions (following roadmap of Chipset vendors).

Additional Shared Hardware

Many important use cases require that a single hardware resource is shared among multiple guests. OpenSynergy provides support for advanced sharing solutions (e.g. shared display and shared GPU).

Contact

OpenSynergy GmbH

Rotherstraße 20
D – 10245 Berlin
Germany

Phone: +49 30 6098 540 - 0
Fax: +49 30 6098 540 - 99
E-mail: sales@opensynergy.com
Web: www.opensynergy.com

OpenSynergy GmbH

Starnberger Str. 22
D-82131 Gauting / Munich
Germany

Phone: +49 89 215 390-73
E-mail: sales@opensynergy.com
Web: www.opensynergy.com

OpenSynergy, Inc. (USA)

2000 Town Center
Suite 1900
Southfield, MI 48075

Phone: +1 (248) 224 9558
E-mail: sales@opensynergy.com
Web: www.opensynergy.com

OpenSynergy, Inc. (USA)

765 East 340 South
Suite 106
American Fork, UT 84003

Phone: +1 (619) 962 1725
E-mail: sales@opensynergy.com
Web: www.opensynergy.com